

APタイプ ガラス管式 エポキシアクリレート樹脂


単位：mm							単位：本		単位：円	
カプセル径 D	品 番	カプセル全長 L	容量 cm ³	使用ボルト 異形棒鋼	穿孔径	穿孔深さ	入数			標準価格 (税抜き)
							小箱	中箱	大箱	
8.0	 AP- 8	70	2.7	M8・W5/16	9.0	70	20	100	1,000	250
10.5	  AP-10	90	6.3	M10・W3/8 D10	12.0 13.0	90				265
13.0	  AP-12	95	9.5	M12・W1/2 D13	14.5 16.0	100				380
17.0	  AP-16	125	21.5	M16・W5/8 D16	19.0 20.0	130			500	650
20.0	  AP-20	195	50.3	M20 W3/4 D19	24.0 22.0 25.0	200	10	50	200	965
24.0	 AP-22	245	90.0	M22・W7/8 D22	28.0 30.0	250	5	20	100	1,540
28.0	  AP-24	280	148.0	M24・W1 D25	32.0 34.0	300		10	50	2,335
35.0	AP-30	330	276.0	M30・W1-1/4 D32	40.0 42.0	350	—	5	30	4,605
40.0	AP-36	400	447.0	M36・W1-1/2 D38	48.0 50.0	400			20	7,420
20.0	  AP-2016	160	41.0	M20 W3/4 D19	24.0 22.0 25.0	160	10	50	200	935

AP-Sタイプ ガラス管式 エポキシアクリレート樹脂

単位：mm							単位：本			単位：円
カプセル径 D	品 番	カプセル全長 L	容量 cm ³	使用ボルト 異形棒鋼	穿孔径	穿孔深さ	入数			標準価格 (税抜き)
							小箱	中箱	大箱	
10.5	AP-10S	65	3.8	M10・W3/8 D10	12.0 13.0	50	20	100	1,000	245
13.0	AP-12S	65	6.0	M12・W1/2 D13	14.5 16.0	60 65				360
17.0	AP-16S	95	14.4	M16・W5/8 D16	19.0 20.0	85			500	605
20.0	 AP-20S	140	32.0	M20 W3/4 D19	24.0 22.0 25.0	130	10	50	200	895
24.0	AP-22S	180	61.0	M22・W7/8 D22	28.0 30.0	165	5	20	100	1,435
28.0	  AP-24S	195	98.0	M24・W1 D25	32.0 34.0	195		10	50	2,165
35.0	AP-30S	220	190.0	M30・W1-1/4 D32	40.0 42.0	230	－	5	30	4,130
40.0	AP-36S	260	293.0	M36・W1-1/2 D38	48.0 50.0	260				6,705

AP-Lタイプ ガラス管式 エポキシアクリレート樹脂

単位：mm							単位：本		単位：円	
カプセル径 D	品 番	カプセル全長 L	容量 cm ³	使用ボルト 異形棒鋼	穿孔径	穿孔深さ	入数			標準価格 (税抜き)
							小箱	中箱	大箱	
10.5	 AP-10L	125	9.2	M10・W3/8 D10	12.0 13.0	120	20	100	1,000	325
13.0	 AP-12L	135	14.9	M12・W1/2 D13	14.5 16.0	145			600	485
17.0	 AP-16L	170	30.0	M16・W5/8 D16	19.0 20.0	185			200	795
20.0	 AP-20L	230	59.3	M20 W3/4 D19	24.0 22.0 25.0	245	10	50	100	1,220
24.0	 AP-22L	280	106.7	M22・W7/8 D22	28.0 30.0	280	5	20	100	1,910
28.0	AP-24L	325	170.0	M24・W1 D25	32.0 34.0	345		10	50	2,895



HP タイプ フィルムチューブタイプ 非スチレン系エポキシアクリレート樹脂

単位：mm							単位：本		単位：円			
カプセル径 D	品 番	全長 L	容量 cm ³	使用ボルト 異形棒鋼	穿孔径	穿孔深さ	入数		標準価格 (税抜き)			
							小箱	大箱				
10.5	  HP-10	120	6.4	M10・W3/8 D10	12.0	90	25	1,000	200			
12.0	  HP-12	130	9.6	M12・W1/2 D13	14.0 16.0	100			295			
15.0	  HP-16	150	18.4	M16・W5/8 D16	18.0 20.0	130		500	485			
18.5	  HP-20	210	41.4	M20 W3/4 D19	23.0 22.0 24.0	200		200	725			
23.0	 HP-22	250	77.7	M22・W7/8 D22	27.0 28.0	250	10	100	1,180			
26.0	  HP-24	300	120.0	M24・W1 D25	30.0 32.0	300	5	50	1,785			
32.0	HP-30	310	190.0	M30 W1-1/4 D32	35.0 37.0 40.0	350			3,525			
12.0	 HP-1213	180	14.9	M12・W1/2 D13	14.0 16.0	130		25	500	365		
15.0	 HP-1616	200	24.6	M16・W5/8 D16	18.0 20.0	160	300		565			
	 HP-1621	220	28.6	M16・W5/8 D16	18.0 20.0	210			685			
18.5	 HP-2025	250	49.3	M20 W3/4 D19	23.0 22.0 24.0	260	200		875			
				  HP-20E	190	34.0			M20 W3/4 D19	23.0 22.0 24.0	160	710
	22.0	 HP-22E	200	56.0					M22・W7/8 D22	27.0 28.0	180	10
	26.0	  HP-24E ※	210	81.0	M24・W1 D25	30.0 32.0			200	5	50	1,680

※受注生産品となります。