


BAタイプ スチール製 ミリねじ：三価クロメート処理
インチねじ：有色クロメート処理



単位：mm										単位：本		単位：円	
ねじの呼び	品 番	アンカー外径 D	全長 L	ねじ長さ ℓ1	スリーブ長さ ℓ2	最大 取付物厚	穿孔径	アンカー 埋込み長さ	穿孔深さ	入数		標準価格 (税抜き)	
										小箱	大箱		
M 6	BA- 650	9.5	50	25	30	8	10.0	30	33	100	600	63	
M 8	 BA- 865	12.0	65	35	35	15	12.5	35	39		400	83	
	 BA- 870		70	40		20				85			
M10	  BA-1070	14.0	70	35	40	11	14.5	40	45	50	300	113	
	  BA-1080		80	45		21					200	117	
	  BA-1010		100	65		41						133	
	  BA-1012		120	85		61						142	
	  BA-1015		150	115		91				30	120	173	
	M12		 BA-1280	17.3		80				35	50	6	18.0
  BA-1210		100	55		26	200							
  BA-1212		120	75		46	206							
  BA-1215		150	105		76	25	100	242					
  BA-1216		160	115		86			255					
  BA-1220		200	155		126			312					
M16	BA-1610	21.7	100	50	50	20	22.0	50	58	20	60	353	
	  BA-1612		120	70	30	60		68	364				
	  BA-1615		150	100	60				395				
	  BA-1616		160	110	70				15	45	406		
	  BA-1620		200	150	110						512		
M20	BA-2016	25.4	160	100	80	40	26.0	80	90	10	30	645	
	BA-2020		200	140		80						756	
W3/8	 BA-3070	14.0	70	35	40	11	14.5	40	45	50	200	113	
	 BA-3080		80	45		21						117	
W1/2	 BA-4100	17.3	100	50	50	26	18.0	50	56	30	120	200	


・ナット / ワッシャー / スプリングワッシャー仕様 ・コンクリート面からのボルト突出寸法目安：全長 - 穿孔深さ
・最大取付物厚＝全長－埋込長さ－（ナット / スプリングワッシャー / ワッシャー）
取付け後にナット上部にネジの余長（3山）が必要な場合は、最大取付物厚から差し引いてください。

SBAタイプ ステンレス製 SUSXM7・SUS304系

単位：mm										単位：本		単位：円	
ねじの呼び	品 番	アンカー外径 D	全長 L	ねじ長さ ℓ1	スリーブ長さ ℓ2	最大 取付物厚	穿孔径	アンカー 埋込み長さ	穿孔深さ	入数		標準価格 (税抜き)	
										小箱	大箱		
M 6	SBA- 650	9.5	50	25	30	8	10.0	30	33	100	600	193	
M 8	 SBA- 865	12.0	65	35	35	15	12.5	35	39		400	275	
	 SBA- 870		70	40		20						275	
M10	  SBA- 1070	14.0	70	40	40	11	14.5	40	45	50	300	330	
	  SBA- 1080		80	50		21					200	344	
	  SBA- 1010		100	70		41						418	
	  SBA- 1012		120	90		61						447	
	  SBA- 1015		150	120		91						537	
	M12		  SBA- 1210	17.3		100					55	50	26
  SBA- 1212		120	75		46	757							
SBA-12125		125				60	36	60	67	784			
  SBA- 1215		150	105		50	76	50	56	25	100	935		
  SBA- 1216		160	115			86					990		
  SBA- 1220		200	155			126					1,210		
M16	SBA- 1610	21.7	100	50	50	20	22.0	50	58	20	60	1,307	
	  SBA- 1612		120	70	30	1,307							
	 SBA-16125		125	75	35	1,360							
	  SBA- 1615		150	100	60	60		68	1,408				
	  SBA- 1616		160	110	70	15		45	1,502				
	  SBA- 1620		200	150	110				1,705				
M20	SBA- 2016	25.4	160	100	80	40	26.0	80	90	10	30	2,558	
	SBA- 2017 ※	27.2	170		75	50	28.0	75	88			2,725	
	SBA- 2020					80						2,827	
M22	SBA- 2220	32.0	200	120	90	62	33.0	90	103	5	15	6,137	
M24	SBA- 2420	34.0		110	100	47	35.0	100	115			7,870	

・ナット / ワッシャー / スプリングワッシャー仕様 ・コンクリート面からのボルト突出寸法目安：全長 - 穿孔深さ
・最大取付物厚＝全長－埋込長さ－（ナット / スプリングワッシャー / ワッシャー）
取付け後にナット上部にネジの余長（3山）が必要な場合は、最大取付物厚から差し引いてください。
※受注生産品となります。

BA-Dタイプ スチール製 溶融亜鉛めっき(ドブめっき)



単位: mm

単位: 本

単位: 円

ねじの呼び	品番	アンカー外径 D	全長 L	ねじ長さ φ1	スリーブ長さ φ2	最大 取付物厚	穿孔径	アンカー 埋込み長さ	穿孔深さ	入数		標準価格 (税抜き)
										小箱	大箱	
M 8	 BA- 865D	12.0	65	35	35	15	12.5	35	39	100	400	100
	 BA- 870D		70	40		20						102
M10	  BA- 1070D	14.0	70	35	40	11	14.5	40	45	50	300	157
	  BA- 1080D		80	45		21					164	
	  BA- 1010D		100	65		41					188	
	  BA- 1012D		120	85		61					196	
M12	  BA- 1210D	17.3	100	55	50	26	18.0	50	56	30	120	269
	  BA- 1212D		120	75		46						306
	BA-12125D		125	105	60	36		60	67	25	100	310
	  BA- 1215D		150			76						316
	  BA- 1216D ※		160	115	86	327						
	  BA- 1220D ※		200	155	126	431						
M16	BA- 1610D	21.7	100	50	50	20	22.0	50	58	20	60	443
	  BA- 1612D		120	70	30	498						
	  BA-16125D		125	75	35	520						
	  BA- 1615D		150	100	60	643						
	  BA- 1616D ※		160	110	70	655						
	  BA- 1620D ※		200	150	110	698						
M20	BA- 2016D ※	25.4	160	100	80	40	26.0	80	90	10	30	1,100
	BA- 2017D ※	27.2	170		75	50	28.0	75	88			1,150
	BA- 2020D ※					80						1,220
M22	BA- 2220D	31.8	200	110	90	62	33.0	90	103	5	15	1,420
M24	BA- 2420D	34.0		100	100	47	35.0	100	115			2,140

・ナット / ワッシャー / スプリングワッシャー仕様 ・コンクリート面からのボルト突出寸法目安: 全長 - 穿孔深さ ※受注生産品となります。

・最大取付物厚=全長-埋込長さ- (ナット / スプリングワッシャー / ワッシャー)

取付け後にナット上部にネジの余長 (3山) が必要な場合は、最大取付物厚から差し引いてください。