



TCW タイプ スチール製 三価クロメート処理

										単位：mm			単位：本		単位：円	
ねじの呼び (外径 D)	品 番	全長 L	本体長さ L1	ねじ長さ ℓ	最大 取付物厚	穿孔径	アンカー有効 埋込み長さ ℓ 1	アンカー 埋込み長さ ℓ 2	穿孔深さ	ナット 二面幅 S	頭部刻印	入数		標準価格 (税抜き)		
												小箱	大箱			
M 6	 TCW- 655	55	24	23	5	6.0	30 以上	38 以上	55-t	10	1	50	800	70		
	 TCW- 670	70		38	20				70-t		4			77		
M 8	 TCW- 860	60	30	23	5	8.0	35 以上	42 以上	55-t	13	1	50	400	79		
	 TCW- 875	75		38	20				70-t		3			95		
M10	  TCW-1070	70	34	27	5	10.0	40 以上	49 以上	65-t	17	1	30	240	98		
	  TCW-1080	80		37	15				75-t		2			105		
	  TCW-1010	100		57	35				95-t		4		180	133		
	  TCW-1012	120		77	55				115-t		5			160		
M12	TCW-1280	80	31	38	5	12.0	45 以上	56 以上	75-t	19	0	25	150	160		
	  TCW-1290	90	39	10	80-t		1	162								
	  TCW-1210	100	49	20	90-t		2	174								
	  TCW-1212	120	69	40	110-t		3	216								
	  TCW-1215	150	99	70	140-t		4	266								
M16	  TCW-1612	120	50	55	15	16.0	64 以上	79 以上	105-t	24	2	10	60	364		
	  TCW-1614	140		75	35				125-t		4			380		

・ナット/ワッシャー/スプリングワッシャー仕様

・t=取付物厚

STCW タイプ ステンレス製 SUS304 系

単位：mm															単位：本		単位：円	
ねじの呼び (外径 D)	品 番	全長 L	本体長さ L1	ねじ長さ ℓ	最大 取付物厚	穿孔径	アンカー有効 埋込み長さ ℓ 1	アンカー 埋込み長さ ℓ 2	穿孔深さ	ナット 二面幅 S	頭部刻印	入数		標準価格 (税抜き)				
												小箱	大箱					
M 8	 STCW- 860	60	30	23	5	8.0	35 以上	42 以上	55-t	13	1	50	400	210				
	 STCW- 875	75		38	20				70-t		3			230				
M10	  STCW-1070	70	34	27	5	10.0	40 以上	49 以上	65-t	17	1	30	240	360				
	  STCW-1080	80		37	15				75-t		2			370				
	  STCW-1010	100		57	35				95-t		4		180	410				
	  STCW-1012	120		77	55				115-t		5			460				
M12	  STCW-1290	90	40	39	10	12.0	50 以上	61 以上	80-t	19	1	25	150	600				
	  STCW-1210	100		49	20				90-t		2			610				
	  STCW-1212	120		69	40				110-t		3		100	690				
	  STCW-1215	150		99	70				140-t		4			820				
M16	  STCW-1612	120	50	55	15	16.0	64 以上	79 以上	105-t	24	2	10	60	1,200				

・ナット/ワッシャー/スプリングワッシャー仕様

・t=取付物厚

TCW-D タイプ 本体: スチール製 溶融亜鉛めっき(ドブめっき) / スリーブ: ステンレス製 SUS304

単位: mm											単位: 本		単位: 円	
ねじの呼び (外径 D)	品 番	全長 L	本体長さ L1	ねじ長さ ℓ	最大 取付物厚	穿孔径	アンカー有効 埋込み長さ ℓ 1	アンカー 埋込み長さ ℓ 2	穿孔深さ	ナット 二面幅 S	頭部刻印	入数		標準価格 (税抜き)
												小箱	大箱	
M 8	 TCW- 860D	60	30	23	5	8.0	35 以上	42 以上	55-t	13	1	50	400	102
M10	 TCW-1070D	70	34	27	5	10.0	40 以上	49 以上	65-t	17	1	30	240	170
	 TCW-1080D	80		37	15				75-t		2			174
M12	  TCW-1290D	90	40	39	10	12.0	50 以上	61 以上	80-t	19	1	25	150	261
	  TCW-1210D	100		49	20				90-t		2			270
	  TCW-1212D	120		69	40				110-t		3		292	
	  TCW-1215D	150		99	70				140-t		4		323	
M16	  TCW-1612D	120	50	55	15	16.0	64 以上	79 以上	105-t	24	2	10	60	567

・ナット/ワッシャー/スプリングワッシャー仕様

・t=取付物厚